


155Mb/s 40 SFP
RTXM182-801 & RTXM182-802



RTXM182-801	RTXM182-802	155Mb/s	LC	SFP	PIN
			EEPROM	-	

LC
3.3V
155Mb/s
PECL
40
: 0°C ~+70°C
RoHS

SFP MSA (INF-8074i)
IEEE802.3ah
ITU-T G.957

		Icc	mA	-	-	300	1		
			mV	150	-	1100			
			mV	300	-	600			
TX_fault /LOS	(TTL)	VOH	V	2.0	-	Vcc			
		VOL		0	-	0.8			
TX_disable	(TTL)	VOH	V	2.0	-	Vcc			
		VOL		0	-	0.8			
155M BIDI SFP									
			Po	dBm	-5	0	EOL		
			λ c	nm	1260	1310	1360	FP-LD	
					1520	1550	1580	DFB-LD	
			EX	dB	10				
(RMS)		$\Delta\lambda$	nm				3	1310nmFP-LD	
(20dB)		$\Delta\lambda$	nm				1	1550nmDFB-LD	
				dB	30				
			Tp-p	ns				1	2
			RIN	dB/Hz				-116	
ITU-T STM1									
			Poff	dBm	-	-	-45		
			λ c	nm	1480				1580
					1260				1360
			S	dBm				-31	
			Pin	dBm	-8				
				dB				-32	
					-45				
				dB	0.5				5
				dB				1	

155Mbps 23

RTXM182-801	SFP	155M	1310nm FP-LD	-5~0 dBm	PIN 1550nm	< -31dBm	0~70°C	40km	STM1 FE
RTXM182-802	SFP	155M	1550nm DFB-LD	-5~0 dBm	PIN 1310nm	< -31dBm	0~70°C	40km	STM1 FE